Features and Benefits

Polycom[®] HDX 4000[™]



	Audio
Polycom 22 kHz StereoSurround™	 2 channels of 22 kHz crystal clear audio
	 Superb clarity to hear the subtleties of every word
	 Easily decipher multiple, simultaneous conversations
	• Distinguish which side of the room people are talking from, just like
	in a real meeting
Audio Error Concealment	 Eliminates audio drop-outs on noisy networks
	 Smooth, consistent verbal communications without interruptions
	 Corrects audio from any system seamlessly
	 Activates automatically, only when needed
Flexibility of headset	 Use headset with microphone for complete privacy
	 3.5mm jack built-in for headset or headphone
Built-in stereo speakers	 Powerful sound from built-in speakers offering rich fidelity from 100 Hz to 22 kHz
Integrated desk phone	Your video device can be used as fully-functional speakerphone
č	 VoIP or analog high quality speakerphone
	Video
True High Definition Video	 Natural high high definition during video call
	 Reduce the technology barriers by seeing people and content in HD resolution
	 720p30 (832 kbps- 4 Mbps)
	 480p (256 – 768 kbps)
Embedded HD camera	Camera is positioned in bezel of monitor for improved visual acuity
	Electronic pan-tilt-zoom allows for flexibility
	 16:9 aspect ratio gives a natural viewing angle
	65° field of view allows for a team view in front of the camera
	 Privacy shutter
Polycom Extreme HD LCD	20.1" high definition LCD for increased desktop landscape
	• Multiple resolutions supported, 1600x1200, 1680x1050, 1600x1000
	1400x1050, 1344x1008, 1344x840, 1280x1024, 1280x960,
	1280x800, 1280x720, 1024x768, 800x600
	 High resolution for split screen video and graphics
Lost Packet Recover (LPR)	 Communications remain intact even on disruptive networks
	 Smooth, continuous video without interruptions
	Maintain active face-to-face contact
	 Accomplish meeting objectives without worrying about the video integrity of public or private networks
	integrity of public or private networks
Dual Monitor Emulation	 Activates automatically, only when needed Most efficient use of a single LCD display
	 View near and far video windows at the same time
	 Alternate layout views supporting near end, far end and content in
	native aspect ratio and resolutions



People+Content™, H.239	Content Sharing Papela and Content both shared in High Definition
People+Content [™] , H.239	People and Content both shared in High Definition Delivery Desploy Content or standards based U 220 ensures
	 Polycom People+Content or standards based H.239 ensures interoperability in the industry
	 Dual images allows the far end to see the presentation and the
	speaker at the same time
	 One touch sharing directly from keypad
	 People+Content Receive (included)
	 People+Content Send (optional)
People On Content™	Optional feature allows for users to become part of their
	presentations
	Using chroma key technology, users can place themselves in front
	of the PC video input source.
	 Perfect for distance education and training
	Retain attention, increase productivity
Adjustable Bandwidth for Content	Flexibility to choose the amount of bandwidth to dedicate to Conten
	or People based upon what is being shown
	 Options include 90% Content/ 10% People; 50% Content/ 50%
	People; 10% Content/ 90% People
	 System will automatically adjust bandwidth allocation when sharing
	content based upon content being shown
	 Very powerful for users who share a wide range of content during a
	video call
	 User adjustable setting can be accessed both during a call and
	outside of a call
	User Interface
Non-disruptive Desktop	 Video UI "floats" on top of PC screen when activated
	 View desktop applications during a video call
Multiple resolutions supported	 12 input video resolutions supported for local display
	Platform Versatility
Internal Multipoint Software	Optional upgrade easily done with a software key
	 Conduct meetings beyond just point-to-point
	 Increase productivity by including key people on the call
	 Adding sites during a call can lead to quick decision making
	 Supports up to 4 video calls in a single conference
Secure FTP, Telnet and Web	 Polycom video systems are the most secure video conferencing
	solutions in the industry
	 All access to the HDX system can be secured including accessing
	the HDX system via web-browser as well as secure telnet and ftp
	access via SSH for secure system administration and application
	connectivity
Advanced Encryption Standard (AES)	Communications are confidential and secure
	 Authentication by the National Institutes of Standards means it's
	credible
	 Built-in, no extra hardware required
H.460 NAT/Firewall Traversal	Standards compliance for traversing NATs and Firewalls
	 Session border controller (V2IU) is only needed at the central
	location and all VSX systems with H.460 can communicate through
	the single V2IU
	 Uses H.460.18 for signaling traversal and call establishment and



IP (H.323, SIP or SCCP), ISDN or Serial Connectivity	IP is standard and you choose the H.320 interface best for your application
	 Choose the right option for your specific network connection Supports UPnP and NAT for automatic setup of conferences
	conducted through firewalls
	 Wide range of IP QoS services to insure call quality and integrity
	 Optional H.320 interfaces include Quad BRI, PRI, V.35, RS-449 and RS-530
Multiple Use RS-232 Port	RS-232 port
	Integrate easily with control panels.
	nteroperability
Part of Polycom's Unified Collaborative	 Remote management through Global Management System[™]
Communications	 RMX Click & View[™] offers a variety of layout templates for multipoint coll right from the system's handhold remote
	 multipoint call right from the system's handheld remote Expand the audience over audio and video with an RMX[™] bridge
	 Extended conferencing with Polycom PathNavigator™
	 Schedule, invite participants and manage conferences easily with
	Polycom Conference Suite
	 Video recording, streaming and archiving with the Polycom RSS
	2000™.
	 Use the Polycom SE200 for management, scheduling and astakaoping
Standards-based	gatekeepingSolid, reliable platform
	 Qualified by independent test labs
	 Interoperates with other vendor's systems
	 Easy to install even in a multi-vendor environment
Baseline Mode	 Set your system to baseline mode, H.261 and G.711, for maximum
	interoperability with legacy video conferencing systems
	 Accessible via web, FTP or on-screen UI for easy access by the natural administrator.
	network administratorCan be turned on and off as needed
Award winning documentation	 hnical Documentation Documentation set includes information about setting up,
Award winning documentation	 Documentation set includes information about setting up, maintaining, and using the system
	 Available at www.polycom.com/videodocumentation
	Searchable PDFs with colorful illustrations
	 Administrators Guide, User's Guide, and Quick Tips available in
	most supported languages
Setup Sheets	 Easy-to-follow graphical instructions for setting up the system and paripherala
	peripheralsIllustrations show both minimal and optional system configurations
	 Shipped with the system for easy access
Administrator's Guide	Comprehensive information for configuring system, including an
	explanation of each administrator setting
	 Descriptions of system features and capabilities
	 Back panel diagrams of all systems with explanations of each
Llear Degumente	connector
	 Instructions for using the web interface Quick Tips one-page document provides quick and easy reference
Llear Documente	
User Documents	for video conferencing tasks
User Documents	User's Guide covers everything you need to know about using the
User Documents	



